MSDS Document

Product High Solids Gray Sandable Primer Spray Paint

1. Chemical Product and Company Identification

Trade Name of this Product High Solids Gray Sandable Primer Spray Paint MSDS ID LP 53379

Manufacturer

Lawson Products, Inc. 1666 East Touhy Avenue Des Plaines, IL 60018 **Contact Name**

Corporate Compliance Team


Phone Number

(847) 827-9666

Emergency Phone

(888) 426-4851

Revision Date 01/17/2001





2. Composition and Information on Ingredients

Ingredient Talc	CAS Number 14807-96-6	Weight % 5.0 %
Phenolic Linseed Alkyd Resin	68122-96-3	
Butane	106-97-8	7.0 %
Propellant: Propane	74-98-6	13.0 %
EthyleneGlycol Monopropyl Ether	2807-30-9	3.0 %
Acetone	67-64-1	16.0 %
Toluene	108-88-3	6.0 %
Ethyl Benzene	100-41-4	4.0 %
Xylene	1330-20-7	19.0 %

Page 2 of 5 Source 02/27/2003 MSDS ID LP_53379 High Solids Gray Sandable Primer Spray Paint

Titanium Dioxide 13463-67-7 8.0 %

3. Hazard Identification

Synergistic Products

N/A N/A

REPRODUCTIVE TOXICITY

See chronic exposure statement.

Synergistic Products

N/A

Irritancy Of Product

Moderate eye irritant.

EFFECTS OF CHRONIC EXPOSURE TO PRODUCT

Possible reproductive hazard.

Carcinogenicity

None of the components in this chemical are listed by IARC, NTP or OSHA as a carcinogen.

TARGET ORGANS AFFECTED

Vapors: Irritating to eyes and respiratory tract. Direct Contact: Irritating to skin and eyes.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE

Heart Disease, Respiratory Disorders

EFFECTS OF OVEREXPOSURE

Eyes: Irritation, Redness, Tearing, blurred vision. Skin: Moderate irritation, dermatitis. Breathing: Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and even asphyxiation. Swallowing: Gastro-intestinal irritation, nausea, vomiting, diarrhea.

Route Of Entry

Skin Eyes Inhalation Ingestion

4. First Aid Information

First Aid Procedures

Give oxygen. Do not induce vomiting. Gastric lavage- Wash eyes and skin with water.

5. Fire Fighting Measures

Flash Point	-2
LEL	1.1
UEL	13

Extinguishing Media

Carbon Dioxide Dry Chemical Sand

Page 3 of 5 Source 02/27/2003 MSDS ID LP_53379 High Solids Gray Sandable Primer Spray Paint

6. Accidental Release Measures

Waste Disposal Method

Prevent waste from contaminating surrounding environment. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with Federal, State and Local regulations.

Material Release Or Spill

Remove all sources of ignition, ventilate. Avoid breathing vapors and remove with inert absorbent.

7. Handling and Storage

Handling Precautions

N/A

Storage

Store in a cool, dry place away from heat and open flame. Keep out of reach of children

Other Precautions

All ingredients marked with an (@) symbol are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40CFRPart372.

Handling Precautions And Equipment

Read and follow contents on product label. Do not store in temperatures above 120 F.

8. Exposure Controls and Personal Protection

Hygienic Practices

Wash hands before eating or using the washroom. Smoke in SMOKING AREAS ONLY.

Other Protective Equipment

Eye wash station and safety showers should be available.

Eye Protection

Safety glasses with side shields.

Clothing

Impermeable clothing should be used to prevent excessive skin contact.

Other PPE

N/A

Protective Gloves

Required for prolonged or repeated contact.

Ventilation

If current ventilation practices are not adequate in maintaining airborne concentrations

Page 4 of 5 Source 02/27/2003 MSDS ID LP_53379 High Solids Gray Sandable Primer Spray Paint

below the established exposure limits, additional ventilation or exhaust systems may be required.

Respiratory Protection

If airborne concentrations exceed recommended exposure limits, a suitable NIOSH respirator should be worn.

9. Physical and Chemical Properties

Physical State Liquid pH N/A Boiling/Cond. Point -47.0

ODOR AND APPEARANCE

Solvent odor, grey color.

10. Stability and Reactivity

Incompatibility

None Known.

Conditions to avoid

Avoid contact with any source of ignition.

Hazardous Decomposition Products

None listed.

Hazardous Polymerization

Will not occur.

11. Toxicological Information

12. Ecological Information

13. Disposal Considerations

14. Transportation Information

OSHA CLASS N/A
PER DOT N/A
DOT Class N/A
PER IMCO N/A
IMCO Classification Number N/A
IATA Classification Number N/A

15. Regulatory Information

Page 5 of 5 Source 02/27/2003 MSDS ID LP_53379 High Solids Gray Sandable Primer Spray Paint

16. Other Information