

Spartan Chemical Company, Inc. **Material Safety Data Sheet**

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

Product Division:

SHINELINE BASEBOARD STRIPPER (AEROSOL)

Janitorial

Product Number: 6097

Spartan Chemical Company, Inc.

Product/Technical 1-(800)-537-8990 Information:

1110 Spartan Drive

Medical Emergency:1-(888)-314-6171 (24 hours)

Maumee OH 43537

Chemical Leak/Spil CHEMTREC 1-(800) 424-9300 (24 hours) Emergency:

PA Ratings:	HMIS Ratings:	
Health: 2 - Moderate		2 - Moderate
Fire: 0 - Minimal	Fire:	0 - Minimal
Reactivity: 1- Slight	Reactivity:	1- Slight
Reactivity: 1- Slight	Reactivity:	Annual Control of the

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z- 1 - A			NTP, IARC
Chemical Name(s) % W	CAS Registry No.	TWA mg/m ³	STEL mg/m ³	CELING mg/m ³	or OSHA Carcinogen	
*2-Butoxyethanol	10-15	111-76-2	120	Not Established	Not Established	No
Isobutane	5-10	75-28-5	Not Established	Not Established	Not Established	No
Monoethanolamine	1-5	141-43-5	6	15 (ACGIH)	Not Established	No
Propane	1-5	74-98-6	1800	Not Established	Not Established	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point:		Vapor Pressure:	Unknown
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Complete
And the same of th	11.2-11.8	Specific Gravity (H ₂ O=1):	
Evaporation Rate (but.ace.=1):	<1	Percent Solid by Weight:	1-3
Physical State:	F		The section of the se
Appearance & Odo	r: Clear, semi-viscou	s liquid lemon scent	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point:	None	Method Used:	ASTM-D56
Flammable Limits:	N/A	Flame Extension:	0": NFPA 30 B Level 1 aerosol
	Water, carbon dioxide, chemical or dry foam		
	Use equipment or shielding required to protect personnel against bursting, rupturing or venting containers.		
Unusual Fire & Explosive Hazards:	At elevated temperatures (54°C/130°F) containers may vent, rupture or burst.		

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes & Oral
Conditions to Avoid:	chemical burns. Harmful con absorbed through the skin. Harmful if swallowed. Symidiarrhea. Inhalation of product mist Combustible. Propellant gaposition may ignite with spardown position only. Contains 2-butoxyethanol which symptoms such as head 2-butoxyethanol may cause data. Contains monoethanolamine repeated exposure.	ritation. Symptoms may include pain, redness and stact may not cause immediate pain. Harmful if ptoms may include pain, nausea, vomiting and may irritate throat and respiratory system. Sees released when can is operated in the upright rk, flame or other heat source. Use can in upside thich may cause central nervous system depression dache; dizziness; nausea and drowsiness. Exposure to blood cell; liver and kidney damage based on animal the which may cause liver and kidney damage with the or clothing. Avoid breathing product vapors or with adequate ventilation. Wash thoroughly after
Conditions Aggravated by Use:	Use of this product may aggravasthma and dermatitis.	vate preexisting eye; skin and respiratory disorders such as

Emergency & First Aid Procedu	
Eyes:	In case of contact; immediately flush eyes with water for at least 15 minutes. Remove contact lenses. Get medical attention if irritation persists.
	In case of contact; immediately wash skin with soap and water. Get medical attention if irritation persists.
Ingestion:	Do not induce vomiting. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation; move person to fresh air. Get medical attention if irritation persists.

▼SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials:	Strong oxidizers
	Hazardous Polymerization:	Will Not Occur
Products:		

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	
	Do not incinerate or puncture aerosol. Dispose of in accordance with state, local or Federal regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

• • • • • • • • • • • • • • • • • • •	Not normally required when good general ventilation is provided. However, if exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use-conditions and chemicals in Section II should be considered.
	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber gloves
Eye Protection(Specify Type):	Splash Goggles
	See 29 CFR 1910.132-138 for further reference.

SECTION IX: SPECIAL PRECAUTIONS

Storing:	Use only in the upside down position. Propellant gases released when can is operated in the upright position may ignite with spark, flame or other heat source. Contents under pressure. Do not use near fire, sparks, or flame. Do not store where temperatures could exceed 120° F.
Other Precautions:	Keep out of reach of children.

© SCC 01/05/2006 SHINELINE BASEBOARD STRIPPER Effective (AEROSOL)

Name:

Ronald T. Cook 01/05/2006

Title:

Manager, Regulatory Affairs

Supercedes: 03/26/2004

Date: Ref: 29 CFR 1910.1200 (OSHA) Changes:

Update Section II

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.