

**Material Safety Data Sheet**

May be used to comply with  
 A & HAZARD Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements

**U.S. Department of Labor**  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)



IDENTITY (as listed on Label and List)  
**ChamPADco Padding Cement**

Note: Blank spaces are not permitted. If any data is not available or no information is available, the space must be marked to indicate that.

**Section I - A Compounded Polyvinyl Acetate Base Adhesive**

Manufacturer's Name <b>Champion Mfg. Co.</b>	Emergency Telephone Number <b>Chemtrac 1-800-424-9300</b>
Address (Number, Street, City, State, and ZIP Code) <b>425 W. 32nd St.</b>	Telephone Number for Information <b>704-333-3797</b>
<b>Charlotte, N. C. 28206</b>	Date Prepared <b>Jan. 2, 1991</b>
<b>P. O. Box 18623, Zip Code 28218</b>	Signature of Preparer (optional)

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
<b>Dibutyl Phthalate CAS No. 84-74-2</b>	<b>5 mg./m<sup>3</sup></b>	<b>5 mg./TWA</b>		<b>Approx. 8.0%</b>

**Dibutyl phthalate listed in this section is subject to the reporting requirements of section 313 of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40CFR372**

**Section III - Physical/Chemical Characteristics**

Boiling Point <b>Water Approx. 212 deg. F.</b>	Specific Gravity (H <sub>2</sub> O = 1) <b>Approx.</b>	<b>1.02-1.08</b>
Vapor Pressure (mm Hg) <b>20 deg. C. Approx. 17.6</b>	Melting Point	<b>N/A</b>
Vapor Density (AIR = 1) <b>20 deg. C. Approx. 0.976</b>	Evaporation Rate (Butyl Acetate = 1)	<b>Not determined</b>

Solubility in Water  
**completely miscible with water. Thin only with water when necessary.**

Appearance and Odor  
**Liquid-White Or Colors (Red- Blue- Green- Yellow) Mild Odor**

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used) <b>N/A</b>	Flammable Limits <b>N/A</b>	LEL	UEL
---	--------------------------------	-----	-----

Extinguishing Media  
**Foam, Dry Chemical, Water Spray, CO<sub>2</sub>**

Special Fire Fighting Procedures  
**Fire fighters should wear self contained breathing apparatus to avoid inhalation of smoke**

**or vapors if material is involved in general fire.**

Unusual Fire and Explosion Hazards  
**Non-flammable --None known**

NFPA Hazard Code: **1 Health, 1 Fire, 0 Reactivity**

**Section V -- Reactivity Data**

Stability	Unstable		Conditions to Avoid
	Stable	X	None Known
Incompatibility (Materials to Avoid)			
None known			

**Hazardous Decomposition or Byproducts**

Under severe thermal degradation - low molecular weight hydrocarbon may be formed.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

**Section VI -- Health Hazard Data**

Route(s) of Entry	Inhalation? Yes	Skin? Yes	Ingestion? Not expected
Health Hazards (Acute and Chronic)			

Eyes - may cause irritation - skin - may be irritating on continued or prolonged contact.

Do not take internally.

Carcinogenicity	NTP? N/A	IARC Monographs? N/A	OSHA Required? Not listed
-----------------	-------------	-------------------------	------------------------------

**Signs and Symptoms of Exposure**

For dibutyl phthalate - swallowing may cause nausea, dizziness - over exposure to hot vapors or mist may cause nose and throat irritation.

Medical Conditions Generally Aggravated by Exposure	Unknown
---	---------

**Emergency and First Aid Procedures**

Eyes - flush with water for fifteen minutes and call physician. Skin - wash with soap and water. If ingested, induce vomiting and call physician at once.

**Section VII -- Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled  
Small spill - clean up with water before allowing to dry out. For large spill, dam up to prevent spread, ventilate area, scoop up material and place in suitable container, and wash up with water.

Waste Disposal Methods  
Incinerate or bury in local landfill in accordance with local, state and federal regulations.

Precautions to be Taken in Handling and Storing  
Prevent from freezing - store between 40° - 90° F. Keep containers closed to prevent drying out and microorganism contamination. Use adequate ventilation.

Other Precautions  
Use with good ventilation when using large volumes, using in small area, or in spraying.

**Section VIII -- Control Measures**

Respiratory Protection (Specify Type)		
Should be worn to prevent inhalation of spray mist or heated vapors.		
Ventilation	Local Exhaust	Special
	Mechanical (General)	Other
Recommended to control mist or vapors: general ventilation for normal use.		
Protective Gloves	Chemical resistant rubber or plastic when necessary	Eye Protection
		Goggles to prevent splashes in eyes.

Other Protective Clothing or Equipment  
As needed to protect skin

Work/Hygiene Practices  
Use with good ventilation - avoid prolong or repeated contact with skin - avoid contact w eyes - do not take internally.